

Tube material

Air

PTFE
I.D. 1,6 x A.D. 3,6 mm

PTFE
I.D. 4,0 x A.D. 6,0 mm

PTFE
I.D. 6,0 x A.D. 8,0 mm

FEP
I.D. 1,6 x A.D. 3,6 mm

FEP
I.D. 4,0 x A.D. 6,0 mm

FEP
I.D. 6,0 x A.D. 8,0 mm

PFA
I.D. 1,6 x A.D. 3,6 mm

PFA
I.D. 4,0 x A.D. 6,0 mm

A.D. 8,0 mm

Ozone

PTFE
I.D. 1,6 x A.D. 3,6 mm

PTFE
I.D. 4,0 x A.D. 6,0 mm

PTFE
I.D. 6,0 x A.D. 8,0 mm

FEP
I.D. 1,6 x A.D. 3,6 mm

FEP
I.D. 4,0 x A.D. 6,0 mm

FEP
I.D. 6,0 x A.D. 8,0 mm

PFA
I.D. 1,6 x A.D. 3,6 mm

PFA
I.D. 6,0 x A.D. 8,0 mm

PFA
I.D. 6,0 x A.D. 8,0 mm

Helium

PTFE
I.D. 1,6 x A.D. 3,6 mm

PTFE
I.D. 4,0 x A.D. 6,0 mm

PTFE
I.D. 6,0 x A.D. 8,0 mm

FEP
I.D. 1,6 x A.D. 3,6 mm

FEP
I.D. 4,0 x A.D. 6,0 mm

FEP
I.D. 6,0 x A.D. 8,0 mm

PFA
I.D. 1,6 x A.D. 3,6 mm

PFA
I.D. 4,0 x A.D. 6,0 mm

PFA
I.D. 6,0 x A.D. 8,0 mm

0 10 20 30 40 50 60 70 90 130 150 200 210 220 260 270 390 400
ml/24 hours